



GA 560

HAPS-Free Contact HHR

Description:

GA560 is a high solids, high heat resistance, solvent based, aerosol contact adhesive. Pressurised metal canister it is portable and ready to use. No compressor is required. **GA560** uses include: bench top lamination, bonding carpet, upholstery, flexible foam, fabric, packaging & is well suited to bond many other substrates including polyethylene sheeting. **GA560** has excellent early grab and aggressive tack. **GA560** exceeds the Australian Standard 2131-1978 heat resistance test making it ideal for heat prone areas. Meets American ASTM D5824-98 Heat resistance for lamination adhesives. **GA560** does not contain chlorinated solvents or CFCs, and is methylene chloride free and HAPS free. After drying the adhesive ingredients meet FDA Regulation 21CFR175.105

Typical Properties:

Solids:	Approx 30%
Flash Point:	Less than 0°C
Colour:	Pale Green.
Odour:	Acetone
Application Temp (ideal):	12°C to 22°C (Min Recommended 8 °C)
Wet Weight Coverage:	Approx 30 to 60 g/m ² for most applications.
Clean Up:	Acetone or MEK Solvent Cleaner.
Shelf Life:	Min 12 months if stored correctly.
Pack Size:	17kg nett in pressurised metal canister.

Keep out of reach of children. Caution Flammable !

Surface Preparation:

Surfaces to be bonded should be clean, dry and free from dust, dirt and any other material that may interfere with the adhesion of the coating. Roughening the surface will also increase the bond strength.

Applications:

GA 560 with suitable hose and gun is ready for use. Apply **GA 560** on both surfaces to be bonded. Allow to become touch dry (10 to 60 sec), surfaces should be joined within 20 minutes after spray application. **Not recommended** for bonding polystyrene foam (use **GA565**), or bonding materials to copper.

For First Aid, Fire, Storage, Disposal, Transport and all other relevant information, refer to SDS sheets.

The representations and recommendations regarding the products are based on tests which we believe to be reliable. However no guarantee of their accuracy can be made because of the great range of field conditions and variations encountered in raw materials, manufacturing equipment and methods. Thus, the products are sold with a limited warranty only, and on the condition that purchasers will make their own tests to determine the suitability of the product for their particular purposes. Under no circumstances will G & A Adhesives Ltd be liable to anyone except for replacement of the products or refund of the purchase price. **All sales are expressly limited to terms and conditions of sale of –**

G & A Adhesives Ltd.

Ph: 09 274 8440 Fax 09 274 8450 Email: sales@gasales.co.nz